

Plan your installation.

A clean finish starts with a clear plan. Measure your wall, prepare the surface and choose suitable fixings.

3000 × 605 × 21 mm · 2 panels / pack · 39.1 sq. ft. / pack

01 Measure & plan

Check wall dimensions, openings and alignment. Each panel measures 3000 × 605 × 21 mm. Use the CAVADOR wall panel calculator to plan full packs.

02 Prepare the wall

Start with a clean, dry, flat and stable indoor wall. For drywall, choose suitable anchors or fix into studs.

03 Cut & dry-fit

Measure before cutting. Cut slats to length with a suitable saw; trim felt between slats with a sharp knife. Dry-fit before fixing.

04 Choose the fixing

Use suitable screws or mounting adhesive. Select fixings for the wall material and the approximate 13.6 kg panel weight; follow their instructions.

05 Finish edges & corners

Plan exposed edges and external corners before fixing. Choose an appropriate finishing strip and confirm its finish and availability with CAVADOR.

06 Care for the finish

Vacuum gently with a soft attachment or use a dry cloth. Keep these MDF panels in dry indoor spaces; do not wash with water.

About acoustic performance

The manufacturer reports NRC 0.80 for 9 mm PET backing. Sound absorption depends on coverage, room surfaces and mounting. Confirm the test documentation and mounting arrangement relevant to your project.

A planning guide. Fixing requirements depend on your wall and installation.

SOURCES

CAVADOR product information INTCO installation guidance INTCO JM1114 profile